

# SAFETY DATA SHEET

## SECTION 1. IDENTIFICATION



Great Lakes Dental Technologies, Ltd.  
200 Cooper Ave  
Tonawanda, NY 14150

716-871-1161  
800-828-7626  
CHEMTREC: 800-424-9300

**Product Name:** Rainbow Resin  
**Product Number:** 045-002, 045-003, 045-004, 045-005, 045-006, 045-007, 045-008, 045-009, 045-010  
045-040, 045-086, 045-087, 045-092, 045-093

Effective Date: 7/6/22

## SECTION 2. HAZARDOUS IDENTIFICATION

### Classifications

Flammable liquids	Category 2
Skin Corrosion / Irritation	Category 2
Skin Sensitization	Category 1
Specific Target Organ Toxicity – Single Exposure	Category 3

### Signal Word

Danger

### Hazard Statements

Highly flammable liquid and vapor  
Causes skin irritation  
May cause an allergic skin reaction  
May cause respiratory irritation



Appearance: Clear

Physical State: Liquid

Odor: Acrid

### **Precaution Statements**

Keep away from heat, sparks, open flames, and hot surfaces. No smoking.  
Keep container tightly closed.  
Ground / bond container and receiving equipment.  
Use explosion – proof electrical, ventilating, lighting, and equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust, fume, gas, mist, vapors, and spray.  
Wash hands thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves, clothing, eye and face protection.

### **Precautionary Statements – Response**

IF ON SKIN (or hair) – Remove / take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED – Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  
If skin irritation or rash occurs get medical advice / attention.  
Take off contaminated clothing and wash before use.  
In case of fire, use CO2 for extinction.

### **Precautionary Statements – Storage**

Store in a well ventilated place. Keep container tightly closed.  
Store in a well ventilated place. Keep cool.

### **Precautionary Statements – Disposal**

Dispose of contents / container in accordance with local regulation.

### **Hazardous Component(s) for Labeling**

Contains Methyl Methacrylate

### **Hazards not otherwise classified (HNOC)**

May be harmful if swallowed

### **Other Information**

Harmful to aquatic life.

### SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Hazardous Components</u>	<u>CAS #</u>	<u>Weight - %</u>	<u>Trade Secret</u>	Specific Chemical Weight
Methyl Methacrylate	80-62-6	>95	*	Withheld as a Trade Secret
N, N-dimethyl-p-toluidine	99-97-8	< 2	*	

### SECTION 4. FIRST AID MEASURES

#### **Eye Contact**

Irrigate with eyewash solution or clean water, holding the eyelids apart for at least 15 minutes. Obtain immediate medical attention if irritation persists.

#### **Skin Contact**

Remove contaminated clothing. Wash skin immediately with water. If symptoms (irritation or blistering) occur obtain medical attention.

#### **Inhalation**

Remove patient from exposure,, remove to fresh air, keep warm and at rest. Obtain immediate medical attention. **Ingestion**

If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Obtain immediate medical attention.

#### **Treatment**

Treat symptoms conventionally, after thorough decontamination.

### SECTION 5. FIRE FIGHTING MEASURES

#### **Suitable Extinguishing Media**

Chemical Foam, Dry chemical, Carbon Dioxide (CO<sub>2</sub>). Water may not be effective.

#### **Special Fire Fighting Procedures**

Highly flammable. When involved in a fire, this product may ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Do not enter fire area without proper protection. Fight fire from a safe location. Heat / impurities may cause pressure to build and/or rupture closed containers, spreading fire, increasing risk of burns / injuries. A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

#### **Unusual Fire / Explosion Hazards**

For bulk size > 1L – high temperatures, inhibitor depletion, accidental impurities or exposure to radiation or oxidizers may cause spontaneous polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during a runaway polymerization. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

### **Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Before cleaning any spill or leak, individuals must wear personal protective equipment as required. Remove any contaminated clothing and wash thoroughly before reuse.

**Environmental precautions** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Prevent product from entering drains. Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

### **Methods and material for containment and clean up**

**Method for containment** Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. DO NOT use combustible material such as sawdust. May contaminate water supply.

**Method for clean-up** Maximize ventilation (open doors and windows) and secure all sources of ignition. Place into appropriate closed containers (s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap.

## **SECTION 7. HANDLING & STORAGE**

### **Storage temperature**

Preferably not exceeding 25 °C.

### **Handling Precautions**

Observe precautions found on the label. Close container after each use. Ground all metal containers when transferring. Use explosion-proof equipment. Avoid contact with skin and eyes. Avoid inhalation of high concentration of vapors. Use only in well ventilated areas. The vapor is heavier than air; beware of pits and confined spaces. Take precautionary measures against static discharges.

### **Storage Precautions**

Keep only in original container. Store in cool, dry place away from heat, sparks, flame, and direct sunlight, other light sources, or sources of intense heat. Keep container closed to prevent water absorption and contamination. Keep away from sources of ignition – no smoking. Methacrylate stored in bulk must be kept in contact with air (oxygen).

### **Further Info on Storage Conditions**

Monomer vapors are uninhibited and may form polymers in vent or flame arresters resulting in blockage of vents.

<b>SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION</b>
---

**Industrial Hygiene**

Avoid contact with skin, eyes, clothing, and prolonged contact with the product. Wash face and hands thoroughly with the soap and water after use and before eating, drinking, smoking, or applying cosmetics. Do not eat, drink, or smoke while handling product.

**Ventilation Measures**

Provide adequate ventilation including appropriate local extraction to ensure that the defined occupational exposure limit is not exceeded.

**Respiratory Protection**

Wear suitable respiratory equipment if exposure to levels above the occupational exposure limit is likely. A suitable mask with filter type A may be appropriate. If necessary, use only respiratory protection authorized by U.S. OSHA's requirement in 29 CFR SS 1910.134 or other appropriate governing standard.

**Hand Protection**

If anticipated that prolonged and repeated skin contact will occur during use of this product, wear chemical resistant gloves for routine industrial use. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR SS 1910.138 or other appropriate governing standard.

**Eye Protection**

Depending on the use of this product, splash or safety glasses or goggles may be worn. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR SS 1910.138 or other appropriate governing standard. Ensure that an eyewash station, sink, or washbasin is available in case of exposure to eyes.

**Skin and Body Protection**

Wear suitable protective clothing. Remove contaminated clothing, washing thoroughly before reuse.

**Additional Protective Measures**

Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

**Occupational Exposure Limits:**

<b>Hazardous Ingredient(s)</b>	<b>PEL(OSHA)</b>	<b>TLV (ACGIH)</b>	<b>Recommendation</b>
Methyl Methacrylate	100 ppm	100 ppm	100 ppm

## SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

- **Form** – Liquid
- **Appearance** – Clear or slightly tinted
- **Odor** –Acrid
- **Evaporation Rate** – (BuAc=1) 3.1
- **Flash Point** – 11.5 °C (52.7 °F) (TCC)
- **Lower Explosion Limit** – 2.12%
- **Upper Explosion Limit** – 12.5%
- **Auto Ignition Temperature** – 421 °C (790 °F)
- **Vapor Density (AIR=1)** – 3.5 @ 15.5 °C (60 °F)
- **Solubility in Water** – 1.6 wt% @ 20 °C (68 °F)
- **Approximate Boiling Range** – 214 °F at 760mm/hg
- **Percent Volatile** – 99+
- **Density** – 0.949 g/ml @ 15.5 °C
- **Specific Gravity (H2O=1)** – 0.94

## SECTION 10. STABILITY & REACTIVITY

**Hazardous Reactions** – Hazardous polymerization may occur.

**Stability** – Unstable / reactive upon depletion of inhibitor.

**Materials to Avoid** – Strong oxidizers, strong reducers, free radical initiators, inert gases, and oxygen scavengers. Material has strong solvent properties and can soften paint and rubber.

**Conditions to Avoid** – Temperatures above 21 °C, 70 °F, localized heat sources (example drum or band heaters) oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing.

**Hazardous Decomposition Products** – Oxides of carbon when burned.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Routes of Exposure

Inhalation – Harmful if inhaled.

Eye Contact – Causes severe eye irritation

Skin Contact – Causes skin irritation

Ingestion – May be harmful if swallowed

<u>Component</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Inhalation LC50</u>
Methyl Methacrylate	7872 mg/mk (rat)	> 5 g/kg (rabbit)	400 ppm (rat) 1 h 4632 ppm (rat) 4 h
N, N-Dimethyl-p-toluidine	1650 mg/k	-	1400mg/m <sup>3</sup> (rat) 4 h

### Symptoms – Physical, chemical, and Toxicological

Contact may cause irritation and redness. Exposed individuals may experience eye tearing, redness, and discomfort. Prolonged exposure in poorly ventilated area may cause respiratory irritation.

### Immediate effects as well as chronic effects from short and long term exposure

#### Sensitization

May cause allergic skin reaction

#### Carcinogenicity

Not classifiable as a human carcinogen

### Methyl Methacrylate

IARC (International Agency for Research on Cancer) – Group 3 IARC components are “not classifiable as human carcinogens.

### STOT – Single Exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

### STOT – Repeated Exposure

No evidence for hazardous properties.

### Numerical Measures of Toxicity – Product

Not determined

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix – Oral** 3,082 mg/kg    **Dermal** 5,107 mg/kg    **Inhalation-dust/mist** 6848 ppm

## SECTION 12. ECOLOGICAL INFORMATION (non-mandatory)

### Aquatic Toxicity – Methyl Methacrylate

- LC50: 130 mg/L, 96H (Flathead Minnows)
- EC50: 69 mg/L, 48H (Daphnia Magna)
- LC50: 170 mg/L, 96H (algae)

### Environmental Fate – Methyl Methacrylate

- 28 day Biodegradation Study – not readily biodegradable.
- Chemical Oxygen Demand (COD) 88% (28 days).
- Inherent Biodegradation – Dissolved Organic Carbon Removal (DOC removal) > 95% (28 days).
- Adsorption / Desorption – High mobility in soil.

## **SECTION 13. DISPOSAL CONSIDERATIONS (non-mandatory)**

### **Waste Disposal Method**

When discarded it is a hazardous waste by the EPA under RCRA. The reportable quantity (RQ) for Methyl Methacrylate is 1000 lbs. (40 CFR Part 302). After addition of excess inhibitor, dispose of waste material in accordance with Federal, State, and Local regulations. Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to residual flammable material, associated with empty containers. Dispose of all empty containers properly in accordance with Federal, State, and Local regulations.

## **SECTION 14. TRANSPORT INFORMATION (non-mandatory)**

- **DOT / UN Shipping Name:** Flammable Liquid, n.o.s.  
(Methyl Methacrylate monomer, stabilized / N,N-dimethyl-p-toluidine solution)
- **NA/UN Number:** UN 1993
- **DOT/UNCLASS:** 3
- **Packing Group:** II
- **Label:** Flammable Liquid
- **IMDG Class:** 3
- **CERCLA RQ:** 1000 lbs

## **SECTION 15. REGULATORY INFORMATION (non-mandatory)**

### **International Inventories**

Methyl methacrylate 80-62-6

**TSCA** Listed United States Toxic Substances Control Act, Section 8(b) Inventory

**DSL** Listed Canadian Domestic Substances List

**EINECS** Listed European Inventory of Existing Chemical Substances

**EU Regulations** EC No. 1272/2008 (CLP) Classification, Labeling, Packaging

### **US Federal Regulations**

SARA 302- Extremely hazardous substance- not listed

SARA 311/312- Hazard categories- listed Methyl methacrylate 80-62-6

SARA 313 - Methyl Methacrylate 80-62-6

**US State Regulations:** California Proposition 65- Warning. This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin: None

**US State Right-to-Know Regulations:** Not established



<b>SECTION 16. OTHER INFORMATION (non-mandatory)</b>
--

HMIS Rating:

- **Health** – 2
- **Flammability** – 3
- **Reactivity** – 2

NFPA Rating

- **Health** – 2
- **Flammability** – 3
- **Reactivity** – 2

0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious, 4 = Severe

\* = Chronic Health Hazard

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the data of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in text.